

2014/11/10

595RS-R

SER	SIZE	PR	LI/SS	OVERALL mm	Diameter in	Section mm	Width in	Standard Rim in	Approved Rim Width	Tread Width mm	Tread Depth in	Weight KG	MAX. PSI cold	Max. Load KGS	LBS	UTQG	Side Wall	P-Code		
30	285/30ZR18		97W XL	626	24.6	290	11.4	10.0	9.5-10.5	259	10.2	8	6.2	13.1	50	730	1609	140AA A	BSW	95HN8AFE
35	245/35ZR18		88W	627	24.7	248	9.8	8.5	8.0-9.0	224	8.8	8	6.5	11.6	44	560	1234	140AA A	BSW	95DM8AFE
	255/35ZR18		90W	634	25.0	260	10.2	9.0	8.5-9.5	236	9.3	8	6.5	12.4	44	600	1323	140AA A	BSW	95EM8AFE
	265/35ZR18		93W	643	25.3	271	10.7	9.5	9.0-10.0	246	9.7	8	6.5	12.8	44	650	1433	140AA A	BSW	95FM8AFE
40	215/40ZR17		83W	603	23.7	222	8.7	7.5	7.0-8.5	190	7.5	9	7.5	10.0	44	467	1074	140AA A	BSW	95AL7AFE
	235/40ZR17		90W	619	24.4	238	9.4	8.5	8.0-9.5	216	8.5	8	6.5	11.3	44	600	1323	140AA A	BSW	95CL7AFE
	255/40ZR17		94W	634	25.0	260	10.2	9.0	8.5-10.0	232	9.1	8	6.5	12.4	44	670	1477	140AA A	BSW	95EL7AFE
40	225/40ZR18		88W	636	25.0	231	9.1	8.0	7.5-8.5	204	8.0	8	6.5	10.9	44	560	1235	140AA A	BSW	95BL8AFE
	235/40ZR18		91W	643	25.3	240	9.4	8.5	8.0-9.0	218	8.6	8	6.5	12.2	44	615	1356	140AA A	BSW	95CL8AFE
45	205/45ZR16		83W	589	23.2	209	8.2	7.0	6.5-7.5	188	7.4	8	6.5	9.7	44	487	1073	140AA A	BSW	95OK6AFE
45	215/45ZR17		87W	625	24.6	219	8.6	7.0	6.5-7.5	196	7.7	8	6.5	10.8	44	545	1201	140AA A	BSW	95AK7AFE
	225/45ZR17		94W XL	633	24.9	230	9.1	7.5	7.0-8.0	206	8.1	7	5.2	11.1	50	670	1477	140AA A	BSW	95BK7AFE
	235/45ZR17		94W	643	25.3	240	9.4	8.0	7.5-8.5	212	8.3	8	6.5	11.8	44	670	1477	140AA A	BSW	95CK7AFE
50	195/50ZR15		82W	577	22.7	200	7.9	6.0	5.5-6.5	176	6.9	8	6.5	9.1	44	475	1047	140AA A	BSW	959J5AFE
	205/50ZR15		89W XL	589	23.2	210	8.3	6.5	6.0-7.0	182	7.2	8	6.5	9.7	50	580	1279	140AA A	BSW	950J5AFE
50	205/50ZR16		87W	610	24.0	210	8.3	6.5	6.0-7.0	182	7.2	8	6.5	9.9	44	545	1201	140AA A	BSW	950J6AFE