

2014/04/07

595RS-R

SER	SIZE	PR	L1/SS	OVERALL Diameter mm in	Section Width mm in	Standard Rim in	Approved Rim Width	Tread Width mm in	Tread Depth in32 mm	Weight KG	MAX. PSI cold	Max. Load KGS LBS	UTQG	Side Wall	Tyres	RR	Wet Grip (dBS)	E_Sound	
30	285/30ZR18		97W XL	626 24.6	290 11.4	10.0	9.5-10.5	259 10.2	8 6.2	13.1	50	730 1609	140AA A	BSW	C1	F	E	72	1
35	245/35ZR18		88W	627 24.7	248 9.8	8.5	8.0- 9.0	224 8.8	8 6.5	11.6	44	560 1234	140AA A	BSW	C1	F	E	72	3
	255/35ZR18		90W	634 25.0	260 10.2	9.0	8.5- 9.5	236 9.3	8 6.5	12.4	44	600 1323	140AA A	BSW	C1	F	E	72	2
	265/35ZR18		93W	643 25.3	271 10.7	9.5	9.0-10.0	246 9.7	8 6.5	12.8	44	650 1433	140AA A	BSW	C1	F	E	72	2
40	215/40ZR17		83W	603 23.7	222 8.7	7.5	7.0- 8.5	190 7.5	9 7.5	10.0	44	467 1074	140AA A	BSW	C1	F	E	72	3
	235/40ZR17		90W	619 24.4	238 9.4	8.5	8.0- 9.5	216 8.5	8 6.5	11.3	44	600 1323	140AA A	BSW	C1	F	E	72	3
	255/40ZR17		94W	634 25.0	260 10.2	9.0	8.5-10.0	232 9.1	8 6.5	12.4	44	670 1477	140AA A	BSW	C1	F	E	72	2
40	225/40ZR18		88W	636 25.0	231 9.1	8.0	7.5- 8.5	204 8.0	8 6.5	10.9	44	560 1235	140AA A	BSW	C1	F	E	72	3
	235/40ZR18		91W	643 25.3	240 9.4	8.5	8.0- 9.0	218 8.6	8 6.5	12.2	44	615 1356	140AA A	BSW	C1	F	E	72	3
45	205/45ZR16		83W	589 23.2	209 8.2	7.0	6.5- 7.5	188 7.4	8 6.5	9.7	44	487 1073	140AA A	BSW	C1	F	E	72	3
45	215/45ZR17		87W	625 24.6	219 8.6	7.0	6.5- 7.5	196 7.7	8 6.5	10.8	44	545 1201	140AA A	BSW	C1	F	E	72	3
	225/45ZR17		94W XL	633 24.9	230 9.1	7.5	7.0- 8.0	206 8.1	7 5.2	11.1	50	670 1477	140AA A	BSW	C1	F	E	72	2
	235/45ZR17		94W	643 25.3	240 9.4	8.0	7.5- 8.5	212 8.3	8 6.5	11.6	44	670 1477	140AA A	BSW	C1	F	E	72	3
50	195/50ZR15		82W	577 22.7	200 7.9	6.0	5.5- 6.5	176 6.9	8 6.5	9.1	44	475 1047	140AA A	BSW	C1	F	E	72	3
	205/50ZR15		89W XL	589 23.2	210 8.3	6.5	6.0- 7.0	182 7.2	8 6.5	9.6	50	580 1279	140AA A	BSW	C1	F	E	72	2
50	205/50ZR16		87W	610 24.0	210 8.3	6.5	6.0- 7.0	182 7.2	8 6.5	9.9	44	545 1201	140AA A	BSW	C1	F	E	72	3